

// Specifications

General

- LED&Button: Status LED, Power Button
- Material:
Shell: V-0(UL-94) Flame retardant PC
Socket: Phosphorus-copper
Plug: Nickel-plated copper
- Voltage & Max Load[‡]:
AC, 100-240V, 50/60Hz, 16 A, 3680 W
- Protocols: IEEE 802.11b/g/n, 2.4 GHz Wi-Fi
- Setup: Bluetooth[†]
- Dimensions: 2.8 * 2.0 * 1.6 in (72 * 51 * 40 mm)

Wireless

- Wireless Standards: IEEE 802.11b, 802.11g, 802.11n
- Frequency: 2.400-2.4835 GHz
- Signal Rate: 72Mbps at 2.4 GHz
- Transmit Power: <20dBm (EIRP)
- Wireless Function: Wireless Client
- Wireless Security: No Security; WEP; WPA-PSK; WPA2-PSK; WPA3

Others

- Package Contents:
Mini Smart Wi-Fi Plug Tapo P110M
Quick Start Guide
- Certifications: CE, RoHS
- Operating Temperature: 0 °C–40 °C
- Operating Humidity: 10%–90%RH, Non-condensing

[‡]Voice control is only supported with certain voice assistants.

[†]Bluetooth is only used for setup.

[‡]The total power of the connected electrical equipment should not exceed the max load current, and maximum power supported varies based on the appliance.

Please do not use in damp environments or outdoors. For more information, please visit <https://www.tapo.com/>

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders.

©2023 TP-Link